



X-Series Label Printer


Powerful, Efficient, Convenient Best for General Purpose




 Supported 1 inch or 0.5 inch inner core ribbon

 Wide range moveable reflective paper sensor

 High print speed upto 8 inch/sec for 203dpi

 Supported 300 meter ribbon roll and 5 inch label roll

 Easy paper and ribbon loading

 Fashion elegant appearance and color



Specifications

| Model | X1 | X1i |
|-----------------------|---|----------------------|
| Printing method | Direct thermal & Thermal transfer | |
| Resolution | 203 DPI (8dots/mm) | 300 DPI(11.8dots/mm) |
| Maximum print speed | 8 IPS(203.2mm/s) | 6 IPS(152.4mm/s) |
| Maximum print width | 4.09"(104mm) | 4.15"(105.6mm) |
| Maximum print length | 157.5"(4000mm) | 78.7"(2000mm) |
| Memory | 8MB Flash ROM,16MB SDRAM | |
| Media | Roll-feed, die-cut, continuous, fan-fold, tags, tickets in plain paper or thermal paper. Width: 4.5"(114mm) max.,0.8" (20mm) min. Supply roll: OD 5"(127mm) max., ID 1"(25.4mm) min. Thickness: 0.08~0.20mm(0.003"~0.0078"), including liner | |
| Ribbon | Wax, Wax/Resin, Resin Ribbon roll: OD 2.75"(70 mm) max. with ID 1"(25.4 mm) core or ID 0.5"(12.7mm) core Max width: 110 mm; Max length: 300 M | |
| Media sensor | Adjustable reflective & Transmissive | |
| Bar Code Types | 1D Barcode : Code 39,Code 93,Code 128,Codabar,EAN-8/13/128,Interleave 2 of 5,UCC-128,UPC A/E 2 and 5 add-on, etc. 2D Barcode : Data Matrix, MaxiCode, PDF417,QR, etc. | |
| Interfaces | RS-232 serial, USB | |
| Power rating | 24 VDC,2.5A | |
| Weight | 2.62KGS | |
| Dimensions | W208 x D310 x H195 mm | |
| Operation environment | Temperature: 32° F ~ +104° F (0° C ~ 40° C) Relative humidity: 5% - 85% non condensing | |
| Storage environment | Temperature: -40° F ~ +140° F (-40° C ~ 60° C) Relative humidity: 5% - 85% non condensing | |
| Optional items | Peeler kit, Internal 100/10 M Ethernet Interface card | |

SHENZHEN ZMIN TECHNOLOGIES CO.,LTD

Website:www.zmin.com.cn